

## Tunnel Light 04-TULP80W-01 (P80W)



### Parameter

|                            |                               |           |
|----------------------------|-------------------------------|-----------|
| Type                       | 04-TULP80W-01                 |           |
| Power                      | 80W                           |           |
| Input Voltage              | AC130-260V , AC100-130V @60Hz |           |
| Power Factor               | 0.8                           |           |
| Light Source               | 1W high power Bridgelux LED   |           |
| LED Qty                    | 80                            |           |
| Luminous Efficiency        | > 80lm/W                      |           |
| Color Temperature          | 3'000k-7'000k                 |           |
| CRI                        | Ra > 75                       |           |
| Beam Angle                 | 120°                          |           |
| Light decay (1'000 hours)  | 3-8%                          |           |
| Protection Grade           | IP65                          |           |
| Shell Material             | Aluminium                     |           |
| Surface color              | Silvery white                 |           |
| Lifespan                   | >50'000 hours                 |           |
| Average Illumination       | Height = 4m                   | > 117 lux |
|                            | Height = 5m                   | > 75 lux  |
|                            | Height = 6m                   | > 52 lux  |
|                            | Height = 7m                   | > 39 lux  |
|                            | Height = 8m                   | > 30 lux  |
| Work Temperature           | -20°C to +50°C                |           |
| Work Efficiency            | > 85%                         |           |
| EXW Price for 1 piece      | 795.00 CHF VAT included       |           |
| EXW Price for + 100 pieces | 720.00 CHF VAT included       |           |